



Product information sheet

- Product Name: **Park It Car Stop**
- Models: 6', 4', 3' long
- Manufacturer: GNR Technologies Inc., manufacturing division of Traffic Logix Inc.,
990 Upton, Lasalle, QC H8R 2T9
Tel.: (514) 366-6116, Fax: (514) 366-6440
- Product Description:
1. Material: compression molded composite of the 100% recycled rubber and polyurethane prepolymer
 2. Physical properties of the rubber composite:
 - a) Density 0.6 oz/cu in (ASTM C642)
 - b) Durometer Hardness 65A ± 7 (ASTM D2240)
 - c) Tensile Strength* minimum 210 psi (ASTM D412)
(* main structural areas)
 - d) Compression deformation 10% at 70psi, 68°F (ASTM D575)
 - e) Brittleness at Low temperature: -40°F (ASTM D746)
 - f) Freeze and thaw when exposed to deicing chemicals (ASTM C672)
no loss after 50 cycles
 - f) Coefficient of thermal expansion: 8×10^{-5} in/in/°F (ASTM C531)
 - g) Weathering 70 hours at 158°F (ASTM D573)
 - hardness retained 100% (± 5%)
 - compressive strength 100% (± 5%)
 - tensile strength 100% (± 5%)
 - elongation retained 100% (± 5%)
 3. Available models: 6', 4' and 3' long
 4. Basic dimensions and nominal weights as per attached drawings
 5. Finishing: Black with durable reflective yellow, blue or white molded in tape as per attached drawings
- Installation methods:
- a) with spikes 14" long (minimum diameter 1/2", recommended 5/8")
 - 4 spikes for 6' model
 - 3 spikes for 4' model
 - 2 spikes for 3' model
 - b) with the lag bolts 6" long with 3" long lead shields (minimum diameter 1/2", recommended 5/8")
 - 4 spikes for 6' model
 - 3 spikes for 4' model
 - 2 spikes for 3' model
 - c) with polyurethane adhesive (recommended PL Premium)

- 300 ml. per 6' model
- 200 ml. per 4' model
- 150 ml. per 3' model

- Components:
- a) 100% recycled rubber from car and truck tires (NR, SBR)
 - b) polyurethane prepolymer for rubber granules
 - c) durable yellow, white or blue molded-in tape covered with the glass beads
- Warranty:
- A three (3) year warranty is provided on the product and a 1 year warranty on the tape, as per the manufacturer's installation instructions.
- Attached Drawings:
- 6' model, drawing No. 34PC02-3
 - 14" rebar spike, drawing No. 05SP01

03/06/2011